



Supreme Solar Projects Pvt.Ltd.

Office & Unit -1: #16/4 & 16/5,Avalahalli,Doddaballapura Main Road,Yelahanka,Bangalore-560064,India
Mob: +91-9513736605 E-mail: info@supremesolar.in Website: www.supremesolar.in

FPC SOLAR WATER HEATERS

<i>Capacity Ltr Per Day</i>	<i>Collector Size in mm</i>	<i>Nos. of Collector</i>
500 LPD	2000*1000	4
750 LPD	2000*1000	6
1000 LPD	2000*1000	8
1500 LPD	2000*1000	12
2000 LPD	2000*1000	16



FPC Solar water heater

Terms and Conditions

Cold water tank height should be minimum 6 feet & maximum 7 feet



Supreme Solar Projects Pvt.Ltd.

Office & Unit -1: #407, RMV 2nd Stage, Devi Main Road, Yelahanka, Bangalore-560094, India
Mob: +91-9632417722, E-mail: info@supremesolar.online, Website: www.supremesolar.online

FPC TECHNICAL SPECIFICATION OF FLAT PLATE COLLECTOR

Section : 1.2mm thick Aluminium

Back sheet : 0.46 mm thick Aluminium

Insulation : Fibre Glass wool with 50mm thick

Foil :0.05 mm thick Aluminium Flat plate collector fins (9 No's): Ultrasonic welded with Nalsun coating.

Riser Pipe: 0.33 mm & 0.6mm for **Header pipe** For Non-PRD

Riser Pipe: 0.5mm & 0.71mm for **Header pipe** for PRD

Glazing: 1000 X 2000 X 4mm clear toughened glass

Glass beading: E.P.D.M. Rubber

Fasteners: Stainless steel

Grommets: E.P.D.M Rubber

Flanges: Brass

Finishing: Powder coating

Tank Specification:

Inner tank thickness: 3 mm for non-pressurized (500LPD TO 1000LPD)

Inner tank thickness: 6 mm for Pressurized (500 LPD TO 1000LPD)

Inner tank material: HRCA sheet with Ceramic coated

Outer tank material: Pre-Coated laminated sheet (colour: half white)/Mirror finish

Side Dish: 4 mm Thickness for Non-PRD

Side Dish: 6 mm Thickness For PRD

Insulation: 50mm thick PUF (Polyurethane foaming)

Support structure: GL with powder coating

Guarantee: 5 years Guarantee for Non-PRD & 2-year Guarantee for PRD